

Ele Inox NEW

The NEW stacker made in Stainless steel suitable for intensive use.

prodotti SAMAG e relative illustrazioni possono essere soggetti a varianti senza preavviso







Ele Inox NEW

The NEW stacker made in Stainless steel suitable for intensive use.

prodotti SAMAG e relative illustrazioni possono essere soggetti a varianti senza preavviso

PERFORMANCE, SAFETY AND STABILITY, HYGIENE AND EASY CLEANING

Main characteristics:

- Frame "B" dimension 800/880 mm and nominal capacity 1300/1500 Kg.
- Duplex and Triplex masts With lift heights up to 5200 mm.
- New Electric Steering For simplicity of movement and an optimal use of the truck also in reduced spaces.
- New Tech LATEST generation of AC power and Can Bus technology.
- New Traction Motor- 2000 W for optimal performance levels, better reliability and greater protection.
- New Expanded Frame By optimizing access to the components, we have designed the opening from the front of the machine and no longer from the side, to reduce damage from bumps and to reduce the possibility of water or other infiltrations.
- Swivel Castor wheels Swivel castors better protected because fitted on the inside of the truck's frame and also more accessible thanks to the new
 container space.
- Double Protection double protection of the electric steering to reduce water infiltrations.
- Protected Hour counter Protected and hermetic to guarantee the best cleaning possibile without any infiltrations.
- Increased Battery Power Possibility of fitting a driving type battery up to 500 Ah 24V and with rapid roll-out from the side.
- Control Box with inbuilt control buttons totally in stainless steel and new microswitch with IP67 protection grade.
- Free Lift Optional Free Lift without mast coming out.



✓ DIMENSIONS AND SPECIAL CAPACITIES ON REQUEST:

SOME OPTIONALS



OPERATOR TRANSPORT PLATFORM



SCALE/PRINTER



LITHIUM BATTERY



USE IN COLD STORE

Туре	Stainless steel forklift trucks	Class	Stainless steel stackers for normal-intensive use
Load capacity (Kg)	1500	Lifting capacity (mm)	4800